

# How to Configure Router's Easy Setup?

It is suitable for : **N100RE, N150RH, N150RT, N151RT, N200RE, N210RE, N300RT, N300RH, N300RH, N300RU, N301RT, N302R Plus, N600R, A702R, A850, A800R, A810R, A3002RU, A3100R, T10, A950RG, A3000RU**

**Application introduction:** In order to improve network security, you can disable SSID broadcast in the web-configuration interface. After disabled SSID broadcast, other devices can find and connect to the SSID again.

Take **N200RE-V3** as an example.

**STEP-1:T**

Connect your computer to the router by cable or wireless, then login the router by entering `http://192.168.0.1` into the address bar of your browser.



Note:

The default access address varies depending on the actual situation. Please find it on the bottom label of the product.

**STEP-2:**

User Name and Password are required, by default both are **admin** in lowercase letter. Click **LOGIN**.

## USER LOGIN

[Forget Password?](#)

**STEP-3: Disabled SSID broadcast**

First, the **Easy Setup** page will turn up for basic and quick settings, including **Internet Setting and Wireless Setting**.

**STEP-4:**

Choose the **WAN Access Type**, enter **User Name, Password** provided by your ISP. Set an encryption method and password for your WiFi network. Click Apply to make the settings work.

**STEP-5:**

For successful connection, the Connect Status will show you connected.