

How to Create Your Whole Home Wi-Fi Network on T10

It is suitable for: T10

Application introduction:

T10 uses several units working together to create seamless Wi-Fi in each of your rooms.

Diagram



Preparation

- Connect the Master to the Internet and configure its SSID and password.
- Ensure that these two Satellites are in factory defaults. If not or uncertain, reset them by pressing and holding the panel T button for five seconds.
- Place all the Satellites near the Master, and ensure that the distance, between the Master and Satellite is limited to one meter.
- Check that all the routers above are applied power.

Method One : By T-button

STEP-1:

Press and hold the panel T button on the Master for about 3 seconds until its state LED blinks between red and orange.



Wait until the state LEDs on the two Satellites also blink between red and orange. It may take about 30 seconds.

STEP-3:

Wait about 1 minute for the state LEDs on the Master to blink green and on the Satellites solid green. In this case, it means the Master is synced to the Satellites successfully.

STEP-4:

Adjust the position of the three routers. As you move them, check that the state LEDs on the Satellites light solid green or orange until you find a good location.



STEP-5:

Use your device to find and connect to any router's wireless network with the same SSID and Wi-Fi password that you use for the Master.

STEP-6:

If you want to view which Satellites are Synced to the Master, log in to the Master via a web browser, and then go to the **Mesh Networking Information** area by choosing **Advanced Setup > System Status.**

TOTO LI	NK Device					The Smartest Network Device
T10 (Firmware V5.9c.291)					Easy Setup	🔥 Language 🔻 🧕 Help
System Status	System Statu	6 3				
Deration Mode	This page shows	the current status and some bas	ic settings of the device.			
Network	•					
5G Wireless	+ WAN LAN	2 LANT				
▶ 2.4G Wireless	•				1	
• QoS	System inform	abon da Galavi	w Mode			
Firewall	System Uptin	ve tday, (ay accus Ihour, 46minutes, 28seconds			
Management	Customer UR	L WWW.b	atolink.net			
	Firmulare Ven	sion V5.9c	291			
	Build Time	2017-6	HG 01.06.09			
	Mesh Network	ing Information				
	ID	Device Name	IP Address	MAC Address		
	1	I10	192.168.0.3	142853003162		
	2	110	192.168.0.4	M28530031db		

Method Two : In Web UI

STEP-1:

Enter the master's configuration page 192.168.0.1 and Select "Advanced Setting"



STEP-2:

Choose **Operation Mode > Mesh Mode**, and then click the **Next** button.

TOTO	NK Device	The Smartest Network Device				
T10 (Firmware V5.9c.291)		Easy Setup 🖌 Language 🔻 🤬 Help				
System Status						
Operation Mode	Operation Mode					
Network	+ This page is used to chan	ge Operation Mode.				
🗢 5G Wireless	•	In this mode, the device is supposed to connect to internet via ADSL/Cable Modem. The				
📚 2.4G Wireless	+ Gateway Mode	connection type can be setup in WAN page by using PPPOE, DHCP client, Static IP.				
QoS	Bridge Mode	In this mode, connect the superior AP/Router by wire, you can bridge the superior's AP/Router wired signal into wireless Wi-Fi signals for Wi-Fi devices.				
Firewall	+	In this mode, you can extend the superior Wi-Fi signal by Repeater setting function under				
Management	+	the Wireless column to increase the coverage of the wireless signal.				
	O WISP Mode	In this mode, all ethernet ports are bridged together and the wireless client will connect to ISP access point. The NAT is enabled and PCs in ethernet ports share the same IP to ISP through wireless LAN.				
	💽 Mesh Mode	In this mode, we can achieve intelligent networking among our devices.				
		Next				
	Cor	ovright © 2017 TOTOLINK Ltd., All Rights Reserved				

STEP-3:

In the Mesh list, select Enable to start sync between the Master and the Satellites.

	TOTO	LINK vork Device					The Smar	test Networ	k Device
	T10 (Firmware V5.9c.2	91)				Easy Setup	A Lar	nguage 🔻	🤬 Help
-	System Status								
æ	Operation Mode		Mesh Mode						
•	Network	+	This page is for Mesh Sma	art Networking settings.					
¢	5G Wireless	+	Mesh	Enable	•				
(î:	2.4G Wireless	+	Add device	Disable Enable					
*	QoS								
ô	Firewall	+						Back	
ф	Management	+							
			I	f the connected device is not de	tected, please re-op	en the Mesh switch	again.		

Copyright © 2017 TOTOLINK Ltd., All Rights Reserved

STEP-4:

Wait 1-2 minutes and watch the LED light. It will react just the same as what's among T-button connection.

Visiting 192.168.0.1, you may check the connection status.

TOTO The Smartest Ne	LINK twork Device					The Smartest Network Device
T10 (Firmware V5.9c	.291)					Easy Setup 🔥 Kanguage 🔻 🤬 H
System Status		System Status	e current status and some t	asic settings of the device		
Network						
5G Wireless	•	WAN LAN2	LAN			
P 2.4G Wireless	•	Susteen Informat	ion			
• QoS		Operation Mode	Gali	way Mode		
Firewall	•	System Uptime	104	Onour, 45minutes, 28seconds		
Management	•	Customer URL	and	totolink.net		
		Firmware Versio	an VS 6	ic 291		
		Build Time	201	1-9-6 01 06 09		
		Mesh Networking	g Information			
		ю	Device Name	IP Address	MAC Address	
		1	110	192 168.0.3	142853003162	
		2	110	192.168.0.4	5428530031db	
				Copyright @ 2017 TOTOLINK Ltd. All R.	attr Reserved	

STEP-5:

Adjust the position of the three routers. As you move them, check that the state LEDs on the Satellites light solid green

or orange until you find a good location.

